

MAB 455 / 455 SB

Weather its for a workshop or in the field – the first choice for metal working!

PERFECT FOR THE WORKSHOP AND ON THE ASSEMBLY LINE

Available with the Swivel Base adjustment device for easy centring even when drilling overhead or on a vertical surface. More information about Swivel Base can be found on page 9.



Magnet indicator

Quick-change drilling system



Permanent internal lubrication



MAB 455/455 SB	
Motor output	1,150 W
Voltage	230 V AC, 50 – 60 Hz
Stroke	160 mm
Magnet dimensions	84 x 168 x 48 mm
Weight	13 kg
Quick-change drilling system	KEYLESS, 19 mm (3/4")
Spindle taper	MT 2
Gear 1 range	250 rpm
Gear 2 range	450 rpm
Permanent internal lubrication	✓
Magnet indicator	✓
MAB 455 230 V	MAB 455 110/125 V
MAB 455SB 230 V	MAB 455SB 110/125 V

Included in delivery	
1 Magnetic core drilling machine	
1 KEYLESS quick-change drilling system 19 mm Weldon (3/4")	
1 Ejector pin ZAK 075, 100	
1 Hard-top case	
1 Safety lashing strap	
1 Ejector drift MT 2	
1 Operating instructions	

Core drill	Twist drill
HSS Ø 40 mm	Ø 18 mm
TCT Ø 50 mm	
Cutting depth:	
30-55 mm	

